

Technical Data Sheet

February 2010
For worldwide use

Q-SEAL 263 Dispensing System

Product Description

Two component pneumatic dispensing system used for metering, mixing and dispensing two component polymer material. It holds one 10 US gallon kit at a time.

Features

- Easy to use
- Uses low air pressure
- Low Maintenance
- Disposable tips
- Pneumatic Lift
- Portable
- No hand mixing required
- Graco reliable
- Shut-off ball valve prevents material leakage

Applications

Two component polymer systems provide superior properties into any application such as their lower V.O.C.'s and their faster cure time. Historically, two component polymer systems have been difficult to be accurately measured and mixed. The 263 dispensing system provides an easy solution, the pump meters the material and the disposable tip mixes it. Thus, providing no errors by the user. The disposable tips allow for very easy maintenance and essentially no cleaning. The two parts of the polymer are kept separate throughout the system up to the disposable mixing nozzle, therefore a long shelf life for the polymer, while it is loaded on the pump, can be obtained.



Attachments

The 263 dispensing system comes with a 25 foot moisture lock hose or a hose sized for your specific requirements.

Customer Service

Chemque Inc.
266 Humberline Dr.,
Rexdale, Ontario M9W 5X1
Canada

T: +1- 416-679-5676
F: +1- 416-679-0511
sales@chemque.com
www.chemque.com

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested method of application and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done at Chemque. All technical assistance and information provided with respect to Chemque's products is subject to Chemque's Terms and Conditions, including the limited warranty therein. Chemque's Terms and Conditions appear on the reverse side of Chemque's credit applications and invoices and are available upon your request. Except as expressly provided in the Terms and Conditions, Chemque excludes all express and implied warranties, representations, conditions and objections, whether statutory or otherwise, concerning the quality of the products of Chemque or their fitness for any particular purpose. It is expressly understood and agreed that the customer assumes and hereby expressly releases Chemque from all liability, in tort, contract, or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind Chemque. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.