

Stranded Copper Conductors Concentric Lay Soft-Drawn Bare Copper



7 Strand Concentric



19 Strand Concentric

Part No.	Electro Tin Plated	Size (AWG)	No. of Strands	CM Area	Approx. Wt. lbs./M ft.
8-7	No	8	7	16,510	51
87T	Yes	8	7	16,510	51
6-7	No	6	7	26,240	81
67T	Yes	6	7	26,240	81
4-7	No	4	7	41,740	127
47T	Yes	4	7	41,740	127
2-7	No	2	7	66,360	204
27T	Yes	2	7	66,360	204
1/0-19	No	1/0	19	105,600	325
1/019T	Yes	1/0	19	105,600	325
2/0-7	No	2/0	7	133,100	410
2/07T	Yes	2/0	7	133,100	410
2/0-19	No	2/0	19	133,100	410
2/019T	Yes	2/0	19	133,100	410
3/0-19	No	3/0	19	167,800	518
3/019T	Yes	3/0	19	167,800	518
4/0-7	No	4/0	7	211,600	653
4/07T	Yes	4/0	7	211,600	653
4/0-19	No	4/0	19	211,600	653
4/019T	Yes	4/0	19	211,600	653
250MCM-19	No	250	19	250,000	772
250MCMT	Yes	250	19	250,000	772

NOTES:

- Sizes up to 1000 MCM are available. Please contact the factory for special requests.
- Harger offers standard reel sizes, however we will cut to specified lengths. Contact factory for reel sizes/put ups.
- 7 strand Bare conductor shall meet the requirements of ASTM B-3 & ASTM B-8.
- 19 strand Bare conductor shall meet the requirements of ASTM B-3 & ASTM B-787.
- 7 strand Tinned Copper conductors shall meet the requirements of ASTM B-3, ASTM B-8 & ASTM B-33.
- 19 strand Tinned Copper conductors shall meet the requirements of ASTM B-3, ASTM B-33 & ASTM B-787.