


## Green Insulated Conductors



7 Strand Insulated



19 Strand Insulated

| Part No. | Size (AWG) | No. of Strands | Jacket Type | CM Area | Approx. Wt. lbs./M ft. |
|----------|------------|----------------|-------------|---------|------------------------|
| 67G      | 6          | 7              | THW         | 26,240  | 105                    |
| 619G     | 6          | 19             | THHN        | 26,240  | 98                     |
| 47G      | 4          | 7              | THW         | 41,740  | 160                    |
| 419G     | 4          | 19             | THHN        | 41,740  | 157                    |
| 27G      | 2          | 7              | THW         | 66,360  | 245                    |
| 219G     | 2          | 19             | THHN        | 66,360  | 240                    |
| 1/019G   | 1/0        | 19             | THHN        | 105,600 | 372                    |
| 2/019G   | 2/0        | 19             | THHN        | 133,100 | 462                    |
| 4/019G   | 4/0        | 19             | THHN        | 211,600 | 716                    |

## Solid & Tinned Copper Conductors Solid Single Soft-Drawn Bare Copper



| Part No. | Electro Tin Plated | Size (AWG) | Diameter | CM Area | Approx. Wt. lbs./M ft. |
|----------|--------------------|------------|----------|---------|------------------------|
| 10       | No                 | 10         | .101     | 10,380  | 31-1/2                 |
| 10T      | Yes                | 10         | .101     | 10,380  | 31-1/2                 |
| 8        | No                 | 8          | .128     | 16,510  | 50                     |
| 8T       | Yes                | 8          | .128     | 16,510  | 50                     |
| 6        | No                 | 6          | .162     | 26,240  | 80                     |
| 6T       | Yes                | 6          | .162     | 26,240  | 80                     |
| 4        | No                 | 4          | .204     | 41,470  | 126                    |
| 4T       | Yes                | 4          | .204     | 41,470  | 126                    |
| 2        | No                 | 2          | .257     | 66,360  | 201                    |
| 2T       | Yes                | 2          | .257     | 66,360  | 201                    |

• 2T can be ordered as stock items #2T-250 (250' standard reel) and #2T-500 (500' standard reel).

### NOTES:

- Green Insulated conductor carries a THW or THHN rating. Other colors available upon request.
- Other sizes are available. Please contact factory for special requests and for reel sizes/put ups.
- Solid soft-drawn conductors shall meet the requirements of ASTM B-3.
- Tinned Solid Copper conductors shall meet the requirements of ASTM B-3 & ASTM B-33.

## Solid Copper-Clad Steel Conductors

### #6 Solid Copper-Clad Steel Dead Soft Annealed



| Part No. | Conductivity | Size (AWG) | Diameter | CM Area | Approx. Wt. lbs./M ft. |
|----------|--------------|------------|----------|---------|------------------------|
| 6CW3D    | 30%          | 6          | .162     | 26,240  | 80                     |
| 6CW4D    | 40%          | 6          | .162     | 26,240  | 80                     |

## Copper Flat Strap Conductors



| Part No. | Width (Inches) | Thickness (Inches) | Actual Gauge | X-Sectional Area (in.2) | Approx. Wt. lbs./M ft. |
|----------|----------------|--------------------|--------------|-------------------------|------------------------|
| CUFS1032 | 1              | .032               | 20           | .0320                   | 124                    |
| CUFS2016 | 2              | .016               | 26           | .0318                   | 123-1/2                |
| CUFS3016 | 3              | .016               | 26           | .0478                   | 186                    |
| CUFS4016 | 4              | .016               | 26           | .0640                   | 247-1/2                |
| CUFS6016 | 6              | .016               | 26           | .0956                   | 372                    |

**NOTES:**

- Most Bare Copper Flat Strap conductors are available tinned. Please add prefix T to part number
- Other sizes of conductors are available. Please contact factory for more sizes and for reel sizes/ put ups.