

Copper Vertical Enhanced Ground Rod Kits



Part No.	Length	Inspection Well	Ultrafill 50# Bag	Tail (Conductor) Type (AWG)	Approx. Shipping Wt. (lbs.)
EGR5WG4/0*	5'	Yes	1	5' - 4/0 Stranded	80
EGR8WG2T	8'	Yes	2	5' - #2 Solid Tinned	135
EGR8WG2/0	8'	Yes	2	5' - 2/0 Stranded	140
EGR8WG4/0	8'	Yes	2	5' - 4/0 Stranded	145
EGR10WG2T	10'	Yes	2	5' - #2 Solid Tinned	185
EGR10WG2/0	10'	Yes	2	5' - 2/0 Stranded	190
EGR10WG4/0	10'	Yes	2	5' - 4/0 Stranded	195
EGR20WG2T	20'	Yes	4	5' - #2 Solid Tinned	320
EGR20WG2/0	20'	Yes	4	5' - 2/0 Stranded	325
EGR20WG4/0	20'	Yes	4	5' - 4/0 Stranded	330

- Other sizes and conductor types available. Contact the factory for details.
- * 5' enhanced ground rods are not UL listed.

APPLICATION NOTES:

- Enhanced grounds are used in high resistivity soil conditions and when low resistance ground electrode systems are critical.
- Conductor is welded 18" down from the top.
- Outside diameter of copper tube is 2-1/8".