

## Copper Sectional Enhanced Ground Rod Kits



cUL us Listed 467

Part No.	Overall Length	Section Length	Inspection Well	Ultrafill 50# Bag	Tail (Conductor) Type (AWG)	Approx. Shipping Wt. (lbs.)
SEGR10WG2T	10'	5'	Yes	2	5' - #2 Solid Tinned	185
SEGR10WG2/0	10'	5'	Yes	2	5' - 2/0 Stranded	190
SEGR10WG4/0	10'	5'	Yes	2	5' - 4/0 Stranded	195
SEGR20WG2T	20'	10'	Yes	4	5' - #2 Solid Tinned	320
SEGR20WG2/0	20'	10'	Yes	4	5' - 2/0 Stranded	325
SEGR20WG4/0	20'	10'	Yes	4	5' - 4/0 Stranded	330
SEGR30WG2T	30'	15'	Yes	6	5' - #2 Solid Tinned	450
SEGR30WG2/0	30'	15'	Yes	6	5' - 2/0 Stranded	455
SEGR30WG4/0	30'	15'	Yes	6	5' - 4/0 Stranded	460
SEGR40WG2T	40'	20'	Yes	8	5' - #2 Solid Tinned	585
SEGR40WG2/0	40'	20'	Yes	8	5' - 2/0 Stranded	590
SEGR40WG4/0	40'	20'	Yes	8	5' - 4/0 Stranded	595

• Other size conductors available. Contact the factory for details.

### APPLICATION NOTES:

- Used where there are vertical height restrictions or when lengths greater than 20' are desired.
- Conductor is welded 18" down from the top.
- Outside diameter of copper tube is 2-1/8".