

Stainless Steel Vertical Enhanced Ground Rod Kits



 us Listed 467

Part No.	Length	Inspection Well	Ultrafill 50# Bag	Tail (Conductor) Type (AWG)	Approx. Shipping Wt. (lbs.)
EGRSS5WG4/0*	5'	Yes	1	5' - 4/0 Stranded	80
EGRSS8WG2T	8'	Yes	2	5' - #2 Solid Tinned	135
EGRSS8WG2/0	8'	Yes	2	5' - 2/0 Stranded	140
EGRSS8WG4/0	8'	Yes	2	5' - 4/0 Stranded	145
EGRSS10WG2T	10'	Yes	2	5' - #2 Solid Tinned	185
EGRSS10WG2/0	10'	Yes	2	5' - 2/0 Stranded	190
EGRSS10WG4/0	10'	Yes	2	5' - 4/0 Stranded	195
EGRSS20WG2T	20'	Yes	4	5' - #2 Solid Tinned	320
EGRSS20WG2/0	20'	Yes	4	5' - 2/0 Stranded	325
EGRSS20WG4/0	20'	Yes	4	5' - 4/0 Stranded	330

- Manufactured from corrosion resistant 300 series stainless steel.
- Other sizes and conductor types available. Contact the factory for details.
- * 5' enhanced ground rods are not UL listed.

APPLICATION NOTES:

- Enhanced grounds are used in high resistivity soil conditions and when low resistance ground electrode systems are critical.
- Excellent for corrosive soils or cathodic protection applications.
- Conductor is welded 18" down from the top.
- Outside diameter of stainless steel tube is 2-3/8".