

## Green Insulated Conductors



7 Strand Insulated



19 Strand Insulated

Part No.	Size (AWG)	No. of Strands	Jacket Type	CM Area	Approx. Wt. lbs./M ft.
67G	6	7	THW	26,240	105
619G	6	19	THHN	26,240	98
47G	4	7	THW	41,740	160
419G	4	19	THHN	41,740	157
27G	2	7	THW	66,360	245
219G	2	19	THHN	66,360	240
1/019G	1/0	19	THHN	105,600	372
2/019G	2/0	19	THHN	133,100	462
4/019G	4/0	19	THHN	211,600	716

## Solid & Tinned Copper Conductors Solid Single Soft-Drawn Bare Copper



Part No.	Electro Tin Plated	Size (AWG)	Diameter	CM Area	Approx. Wt. lbs./M ft.
10	No	10	.101	10,380	31-1/2
10T	Yes	10	.101	10,380	31-1/2
8	No	8	.128	16,510	50
8T	Yes	8	.128	16,510	50
6	No	6	.162	26,240	80
6T	Yes	6	.162	26,240	80
4	No	4	.204	41,470	126
4T	Yes	4	.204	41,470	126
2	No	2	.257	66,360	201
2T	Yes	2	.257	66,360	201

• 2T can be ordered as stock items #2T-250 (250' standard reel) and #2T-500 (500' standard reel).

### NOTES:

- Green Insulated conductor carries a THW or THHN rating. Other colors available upon request.
- Other sizes are available. Please contact factory for special requests and for reel sizes/put ups.
- Solid soft-drawn conductors shall meet the requirements of ASTM B-3.
- Tinned Solid Copper conductors shall meet the requirements of ASTM B-3 & ASTM B-33.